

Product data sheet

R guide rail TS 5000 *



With electrical hold-open device, smoke switch control unit
and lever

AREAS OF APPLICATION

- Single leaf doors
- Hold-open systems with integrated hold-open device and smoke switch
- Installation on hinge side
- Right and left single-action doors



PRODUCT FEATURES

- Electric hold-open device in the guide rail with hold-open area of 80°-130°
- Retention force of the electromechanical hold-open device can be variably adjusted
- Integrated smoke switch control unit
- Smoke switch with contamination indicator and adaption of the alarm threshold
- Additional smoke detectors can be fitted
- Operating voltage 230 V AC
- Horizontally adjustable in the installation position by 4 mm through elongated holes
- With screwed slide block

TECHNICAL DATA

Productname	R guide rail TS 5000 *
Supply voltage	230 V AC
Input voltage	230 V AC
Frequency of supply voltage	50/60 Hz
Duty rating	100 %
IP rating	IP20
Standard conformity	EN 1155
Approvals	General building approval from DIBt as a hold-open system
Length	745 mm
Width	55 mm
Height	30 mm
opening restrictor upgradable	Yes
Hold-open function	Electrical
Hold-open device can be overridden	Yes
Hold-open range	80 ° - 130 °
Smoke switch integrated	Yes
Contamination indicator	Yes
Adaption of the alarm threshold	Yes
Integrated power supply	Yes
Height correction possible	Yes
Flexible opening restrictor	Yes

R guide rail TS 5000 *



VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Supply voltage	Dimensions
R guide rail TS 5000 *	with electric hold-open device, integrated smoke switch control unit and lever	116304	according to RAL	230 V AC	745 x 55 x 30 mm
R guide rail TS 5000 *	with electric hold-open device, integrated smoke switch control unit and lever	116303	Stainless steel optic	230 V AC	745 x 55 x 30 mm
R guide rail TS 5000 *	with electric hold-open device, integrated smoke switch control unit and lever	116300	silver-coloured	230 V AC	745 x 55 x 30 mm
R guide rail TS 5000 *	with electric hold-open device, integrated smoke switch control unit and lever	116302	white RAL 9016	230 V AC	745 x 55 x 30 mm

ACCESSORIES

FLEXIBLE OPENING RESTRICTOR

For E and R guide rails, single and double leaf



Designation	Description	Ident-No.
Flexible opening restrictor	for guide rail 1-leaf: TS 5000 E/R/RFS (door leaf installation), Boxer E; 2-leaf: all E/R/ISM variants TS 5000 (incl. VPK) and Boxer	145311

INSTALLATION MATERIAL

MOUNTING PLATE GUIDE RAIL *

For R and RFS guide rail



Designation	Description	Ident-No.	Colour
Mounting plate guide rail	for R / RFS-guide rail	123296	silver-coloured
Mounting plate guide rail	for R / RFS-guide rail	123297	according to RAL

R guide rail TS 5000 *



* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.