

Product data sheet

Closer body TS 5000 L

SoftClose *



For opposite hinge side EN 3-6 overhead door closer with guide rail with individually adjustable closing speed of 0-15° door opening angle

AREAS OF APPLICATION

- Fire and smoke protection doors
- Right and left single-action doors
- Single-action doors up to 1400 mm leaf width
- Door leaf installation opposite hinge side and transom installation hinge side

Closer body TS 5000 L SoftClose *



PRODUCT FEATURES

- Closing force can be variably adjusted from the front
- Visual closing force display ensures correct setting
- Closing speed can be adjusted from the front via valve
- Latching action / smooth latching function can be adjusted from the front via valve
- Back check can be adjusted from the front via valve
- Door closer, can be used for right and left hand doors
- Minimal installation effort due to low number of individual parts and quick setting

TECHNICAL DATA

Productname	Closer body TS 5000 L SoftClose *
Closing force in accordance with EN 1154	EN 3 - 6
Leaf width (max.)	1400 mm
Type of installation	Door leaf installation opposite hinge side, Transom installation hinge side
Opening angle (max.)	120 °
Identical design for DIN left and DIN right	Yes
Standard conformity	EN 1154:1996/A1:2002/AC:2006
Suitability for fire protection doors	Yes
Length	287 mm
Width	47 mm
Height	60 mm
Closing force adjustable	Yes, stepless
Adjustable closing speed	Yes
Latching action adjustable	Yes, via valve
Latching action speed, adjustable	Yes
Back check integrated	Yes, hydraulically adjustable
Position of closing force adjustment	Front
Visual closing force display	Yes
Safety valve against overload	Yes
Thermo-control valves	Yes
Smoke switch integrated	No

Closer body TS 5000 L SoftClose *



VARIANTS / ORDER INFO

Designation	Description	Ident- No.	Colour	Closing force in accordance with EN 1154	Dimension s
TS 5000 L SoftClose door closer *	Closing force EN 3-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	191210	according to RAL	EN 3 - 6	287 x 47 x 60 mm
TS 5000 L SoftClose door closer *	Closing force EN 3-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	191272	Stainless steel optic	EN 3 - 6	287 x 47 x 60 mm
TS 5000 L SoftClose door closer *	Closing force EN 3-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	191211	white RAL 9016	EN 3 - 6	287 x 47 x 60 mm
TS 5000 L SoftClose door closer *	Closing force EN 3-6, with back check and integrated latching action speed with variable adjustment, for door deceleration (without guide rail and lever)	191209	silver- coloured	EN 3 - 6	287 x 47 x 60 mm

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.